

Guide to Estimating Subgrade Soil Strengths for Fine-Grained Soils

Estimated Consistency		Test By:				Correlates to:			
Feel	Visual	Standard Penetration Test (blows/ft)	Dynamic Cone Penetrometer (in/blow)			Shear Strength, C _u		R Value	CBR
			SC,SM,SP	CL	CH	(psi)	(tsf)		
Very Soft	Man standing sinks > 3"	< 2	-	-	-	< 1.7	< 1.125	-	< 0.4
Soft	Man walking sinks about 2" - 3"	2 - 4	-	-	-	1.7 - 3.5	0.125 - 0.25	< 0.36	0.4 - 0.8
Medium	Man walking sinks about 1"	4 - 8	-	> 2.6	-	3.5 - 6.9	0.25 - 0.5	0.36 - 2.5	0.8 - 1.6
Stiff	Pickup truck ruts about 0.5" - 1"	8 - 15	> 3.9	2.6 - 1.8	-	6.9 - 13.9	0.5 - 1.0	2.5 - 6.8	1.6 - 3.2
Very Stiff	Loaded dump truck ruts about 1" - 3"	15 - 30	3.9 - 2.2	1.8 - 1.3	> 4.3	13.9 - 27.8	1.0 - 2.0	6.8 - 15.5	3.2 - 6.4
Hard	Insignificant ruts from loaded dump truck	> 30	2.2 - 1.1	1.3 - 0.9	4.3 - 2.1	> 27.8	> 2.0	> 15.5	> 6.4

References: After Portland Cement Association, E.I. DuPont literature and McCarthy, David F. Essentials of Soil Mechanics and Foundations. AASHTO, 1993 Guide for Design of Pavement Structures, Van Till et. Al. NCHRP 128.



All information contained herein has been prepared for the benefit of customers interested in US Fabrics' products and is provided as a service to the user. All information and recommendations were carefully compiled and reviewed prior to publication to the best of US Fabrics' knowledge. Final determination of the suitability of any information, material and recommendations for applications contemplated is the sole responsibility of the user.

3-29-16